

CELLSENSE[®] ULTRA WITH XACT ID[™]

Intelligent Detection Starts Here

Intelligent contraband detection re-imagined for today's contraband detection needs, and designed to get smarter over time for future needs.

1 UNIFORM DETECTION

Intelligent detection results in 70% greater detection than our current market-leading product

2 ENVIRONMENTAL NOISE FILTERING

Effective mitigation of background environmental noise, resulting in fewer nuisance and false alarms

3 SIMPLE, RUGGED INTERFACE

Simple, intuitive PCAP touch screen to control all audible, visual, and user settings quickly and effectively

4 LONG BATTERY LIFE

Li-lon battery to extend battery life and performance, including faster charging and auto power-save

5 5-ZONE LED-LIGHTED PRECISION

5 separate zones to indicate location of object and improve search efficiency, all without compromising sensitivity of detection

6 ACTIONABLE DATA

Centralized data analysis and event reporting to ensure compliance with operational standard operating procedures 5

6

9

4

SECURE CONNECTIVITY

Secure ethernet for remote management and integration with third-party data management systems

POWER OPTIONS

Battery, 24V DC Charger or Power over Ethernet (PoE)

ENHANCED LOWER-BODY DETECTION

17X higher detection of ground-level contraband (shoes, pant legs)



PRODUCT SPECIFICATIONS

PHYSICAL AND PERFORMANCE CHARACTERISTICS

Dimensions: Sensor Unit (WxHxD)	3.7 in. x 72 in. x 4.7 in. 9.4 cm x 183.5 cm x 10.6 cm
Weight	Sensor unit: 22 lbs/10 kg Base: 28 lbs/13 kg
User Interface	4.3 in./10.92 cm color touch screen with backlight PCAP touch technology
Connectivity	Ethernet Dry contact relay 24V AC/40V DC Wi-Fi (optional) Bluetooth (optional)
Audible Alert	Variable volume and tone controls
Visual Alert	360° beacon alarm indicator Signal strength: 5 LED levels (front facing) Zone location: 5 LED levels (front facing)
Power	Battery: Integrated Li-Ion Charger: 24V DC Run Time: 16+ hours Charge Time: 3 hours Alternative Power: Power over Ethernet (PoE)

USER ENVIRONMENT	
Operating Temperature	-5°F to 120°F (-20°C to +60°C)
Charging Temperature	32°F to 104°F (0°C to +40°C)
Relative Humidity	95% non-condensing
IP Rating	IP65

DATA OUTPUT AND SECURITY

System Management and Data Collection

Published API for third-party integrations Cybersecure

PERIPHERALS AND ACCESSORIES

Mounting Options

Portable, freestanding base (included)



Metrasens has

re-engineered its market-

leading contraband detection systems to revolutionize portable screening of concealed inmate contraband. By introducing advanced, proprietary software and enhanced sensor design, Cellsense Ultra demonstrates high levels

of detection with low extraneous alarms.

North America and Latin America 630-541-6509

UK, Europe, Middle East, Asia-Pacific +44 (0) 1684 219000

www.metrasens.com info@metrasens.com

©Metrasens. All rights reserved 2021